


Republic of the Philippines DEPARTMENT OF EDUCATION Region XI SCHOOLS DIVISION OF DIGOS CITY





Company Name			DEO M	25.03.022	
Addrage		RFQ No. 25-03-032 Date: March 7, 2025			
Address Contact No.	Date and Time of Opening: March 13, 2025				
TIN No.					
	lowest price on the item/s listed below, subject to the General Conditions, stating the shortest time quotation duly signed by your representative.				
NOTE / INSTRUCTIONS 1. ALL ENTRIES MUST B		MARIA GENE	VIEVE T F	RANCISQUETI	ž.
	UST BE WITHIN 10 DAYS UPON RECEIPT OF PURCHASE ORDER.		C CHAIRPER		
	DEPED-SCHOOLS DIVISION OF DIGOS CITY	For and in the absence of the BAC Chairperson:			
PRICE VALIDITY MUS	T BE WITHIN THIRTY (30) DAYS.		9	•	
	TITEM AND TOTAL AMOUNT	CLAR	ENCE S PU	LLERIN	
	A PHYSICAL STORE WITH READILY AVAILABLE SUPPLIES IN CASE IN NEED		TCE-CHAIRP		
OF POST-QUALIFICA					
	BY THE BUREAU OF PHILIPPINE STANDARDS' (BPS) MANDATORY PRODUCT IES, WHETHER LOCALLY MANUFACTURED OR IMPORTED, ARE REQUIRED TO				
	TANDARD (PS) MARK OR IMPORT COMMODITY CLEARANCE (ICC).				
	IT CERTIFIED PHOTOCOPY OF THE FOLLOWING				
REQUIRED DO	CUMENTS TOGETHER WITH THE RFO:				
	a) Mayor's/Business Permit b) PhilGEPS Registration				
	c) Tax Clearance				
	d) Bank Account Number (Photocopy of any Proof of Bank Account)				
NOTE: For CY	2025, bidders shall submit these documents to DepEd Digos City Division only ONCE.				
10. APPROVED BUDGET FOR THE	Thirty Nine Thousand Two Hundred Thirty Eight Pesos and 78/100 Only	₱39,238.78			
CONTRACT:	(FAILURE TO DO SO WILL MEAN DISQUALIFICATION OF YOUR	BID PROPOSA	AL)		
ITEM NO.	ITEM & DESCRIPTION	QTY.	UNIT	UNIT PRICE	TOTAL PRI
Lot 1	Procurement and Delivery of:				
	Disaster Preparedness Equipment in Schools	-			
	Portable power station, with minimum specifications:	1	unit	_	
	Built-in battery: LMFP with minimum battery capacity: 26.25V 21Ah, 551.25Wh/	<u> </u>	une		
	147000mAh,				
	DC output: 12V DC output *2/10A, Cigarette Lighter*1, USB				
	Output: QC 3.0 output*2, PD18W*1, Unidirectional PD100W*1,	-			
	AC output: 2* 110V230V-50/60Hz 700W (Peak 1200W) / pure sine wave, AC input: 600W,	-			
	MPPT input: 180W,				
	Charging time: 1 hour				
	Weight: 7.5kg,				
	Dimensions: L 23.8, W 19.6, H 28.5 (cm),	1		-	
	LED light: 6W LED light, red/white warning light, AC version: US/JP/EU/UK/CN/AU/CH/KR.	+	-	-	
	SKU: PH3022115, and	1			
	With warranty				
	Portable Two-way radio pocket size, with minimum specifications:	10	piece		
	Frequency range: 400-470MHz Channel capacity: 16	-	-	 	
	Antenna: Integrated antenna	1		1	
	Antenna impedance: 50				
	D: A DOVETIVOS				
	Dimension: 96X55X22mm				
	Transmitter:				
	Transmitter: Output power: 5W				
	Transmitter:				
	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh				
	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features:				
	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features: 50 CTCSS/105 CDCSS				
	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features: 50 CTCSS/105 CDCSS VO.X Function, Voice Prompt, PC Programming, Emergency Alarm, Intelligent				
	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features: 50 CTCSS/105 CDCSS	nd			
	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features: 50 CTCSS/105 CDCSS VO.X Function, Voice Prompt, PC Programming, Emergency Alarm, Intelligent Charging, Battery Save, Low Voltage Alert, and Time-out Timer	nd d			
	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features: 50 CTCSS/105 CDCSS VO.X Function, Voice Prompt, PC Programming, Emergency Alarm, Intelligent Charging, Battery Save, Low Voltage Alert, and Time-out Timer In cities with buildings obstructing, the communication distance is 800-1000M, and	nd d			
	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features: 50 CTCSS/105 CDCSS VO.X Function, Voice Prompt, PC Programming, Emergency Alarm, Intelligent Charging, Battery Save, Low Voltage Alert, and Time-out Timer In cities with buildings obstructing, the communication distance is 800-1000M, an in open outdoor environments, the maximum communication distance is 3KM.	nd	GI	RAND TOTAL:	
	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features: 50 CTCSS/105 CDCSS VO.X Function, Voice Prompt, PC Programming, Emergency Alarm, Intelligent Charging, Battery Save, Low Voltage Alert, and Time-out Timer In cities with buildings obstructing, the communication distance is 800-1000M, and			RAND TOTAL:	r General Condi
	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features: 50 CTCSS/105 CDCSS VO.X Function, Voice Prompt, PC Programming, Emergency Alarm, Intelligent Charging, Battery Save, Low Voltage Alert, and Time-out Timer In cities with buildings obstructing, the communication distance is 800-1000M, an in open outdoor environments, the maximum communication distance is 3KM.		carefully read		
Canvassed by:	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features: 50 CTCSS/105 CDCSS VO.X Function, Voice Prompt, PC Programming, Emergency Alarm, Intelligent Charging, Battery Save, Low Voltage Alert, and Time-out Timer In cities with buildings obstructing, the communication distance is 800-1000M, an in open outdoor environments, the maximum communication distance is 3KM.		carefully read	and accepted you	
anvassed by:	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features: 50 CTCSS/105 CDCSS VO.X Function, Voice Prompt, PC Programming, Emergency Alarm, Intelligent Charging, Battery Save, Low Voltage Alert, and Time-out Timer In cities with buildings obstructing, the communication distance is 800-1000M, an in open outdoor environments, the maximum communication distance is 3KM.		carefully read I/We quote y	and accepted you	
Canvassed by:	Transmitter: Output power: 5W The maximum deviation 5kHz Residual radiation: 60dB Current: 1000mAh Features: 50 CTCSS/105 CDCSS VO.X Function, Voice Prompt, PC Programming, Emergency Alarm, Intelligent Charging, Battery Save, Low Voltage Alert, and Time-out Timer In cities with buildings obstructing, the communication distance is 800-1000M, an in open outdoor environments, the maximum communication distance is 3KM. SUBJECT TO WITHHOLDING TAX		carefully read I/We quote y	and accepted you you on the item/s	

Printed Name/Signature of Authorized Representative

Date: